

HIGH-FREQUENCY COMPOSITE SWITCH MODULE

Publication number: JP2002118487

Publication date: 2002-04-19

Inventor: SATOU HIROKI; TSURUNARI TETSUYA; MURAKAMI KOZO; OMORI YOSHIHARU; HAYAMA MASAOKI

Applicant: MATSUSHITA ELECTRIC IND CO LTD

Classification:

- International: H01L25/00; H01P1/10; H03H9/25; H03H9/72; H03K17/00; H04B1/48; H04B1/50; H04B1/40; H01L25/00; H01P1/10; H03H9/00; H03K17/00; H04B1/44; H04B1/50; H04B1/40; (IPC1-7): H04B1/48; H01L25/00; H01P1/10; H03H9/25; H03H9/72; H03K17/00

- European: H04B1/48; H04B1/50

Application number: JP20000307276 20001006

Priority number(s): JP20000307276 20001006

Also published as:

EP1233528 (A1)
WO0232001 (A1)
US6759925 (B2)
US2003048154 (A)

Report a data error here

Abstract of JP2002118487

PROBLEM TO BE SOLVED: To provide a small/short high-frequency composite switch module which handles the signal of one or more transmission reception systems with different passbands. **SOLUTION:** A wave branching/synthesizing circuit, a switch circuit, and a low-pass filter are main components. They are formed in a laminated body comprising an electrode pattern and a dielectrics layer. At least on the laminated body, elastic surface wave filters corresponding to a plurality of passbands and a part of the switch circuit are provided. A space is formed where the elastic surface wave filter is allowed for elastic surface wave oscillation by a lid provided on its surface, which is sealed for air tightness.

